

JISAN HEAVY INDUSTRY LTD.
Professional Excavator Attachment Manufacturer



Address: NO 41, Jinfeng Road, Fushan District, Yantai, China. 265500
Tel: +86 18615951533 Fax: +86-5353468305
E-mail: scottning@jisanbr.com Website: www.jisanbr.net
Facebook: www.facebook.com/jisanheavyindustry



HYDRAULIC ROTATING ROCK GRAPPLE



Item	Model	Unit	DLKL03	DLKL04	DLKL06	DLKL08	DLKL10	DLKL14	DLKL20
Weight		Kg	320	390	740	1380	1700	1900	2100
Max jaw opening		M/m	1300	1400	1800	2300	2500	2500	2700
Oil pressure		Kg/cm ²	110-140	120-160	150-170	160-180	160-180	180-200	180-200
Set up pressure		Kg/cm ²	170	180	190	200	210	250	250
Operating flux		L/min	30-55	50-100	90-110	100-140	130-170	200-250	250-320
Cylinder Volume		Ton	4.0 x 2	4.5 x 2	8.0 x 2	9.7 x 2	12 x 2	12 x 2	14 x 2
Suitable excavator		Ton	4-6	7-11	12-16	17-23	24-30	31-40	41-50

HYDRAULIC ROTATING LOG GRAPPLE

- ◆ Light weight with wide opening jaws show outstanding performance of grabbing as well as maximizing operating efficiency
- ◆ Maximum grapple opening from 1300mm to 2400mm depending on different models
- ◆ Full 360 degree hydraulic rotation
- ◆ New generation of worm gear design adopted to realize brake function.
- ◆ Made of wear resistance steel and equipped with large cylinder that extend working life, enhance productivity on the jobsite.
- ◆ High-performance check valve utilized to ensure the operator's safety
- ◆ Versatile applications include handling of stone, log, piping, steel bar, marble blocks and disposable waste and many others.



Item	Model	Unit	DLKL03	DLKL04	DLKL06	DLKL08	DLKL10	DLKL14	DLKL20
Weight		Kg	320	390	740	1380	1700	1900	2100
Max jaw opening		M/m	1300	1400	1800	2300	2500	2500	2700
Oil pressure		Kg/cm ²	110-140	120-160	150-170	160-180	160-180	180-200	180-200
Set up pressure		Kg/cm ²	170	180	190	200	210	250	250
Operating flux		L/min	30-55	50-100	90-110	100-140	130-170	200-250	250-320
Cylinder Volume		Ton	4.0 x 2	4.5 x 2	8.0 x 2	9.7 x 2	12 x 2	12 x 2	14 x 2
Suitable excavator		Ton	4-6	7-11	12-16	17-23	24-30	31-40	41-50

